



Care & Maintenance for Urethane Sealed Interior Concrete

Stained concrete offers a floor that is unique and one-of-a-kind. With a little maintenance your stained concrete floor will last for many years

Protecting Your Floor during Construction

If additional construction will be continued on the floor, the surface must be left to cure for 2 days before covering. The floor can then be covered with construction paper. Do not tape directly onto the finished flooring surface with any tape, including painters tape. Only construction paper should be used. Plastic will trap moisture.

Recommended Scheduled Maintenance

General Cleaning

The sealer used on your floor is a very advanced water-based urethane coating that outlasts typical floor finishes 3 to 4 times. General cleaning can be done with a dust mop or vacuum. We find that using a product such as Bruce's hardwood floor and laminate cleaner with a microfiber pad works best for deeper cleaning. A variety of cleaners and finishes can be used to maintain your floor. Always test a new cleaner in an inconspicuous spot to confirm compatibility. You never have to apply a wax to our urethane sealed floors.

Protection

- Use walk off mats at entrance doors and in front of kitchen sink. Avoid rubber backed or other non-ventilating mats or rugs.
- Install proper protectors under the feet of furniture. Caster wheeled chairs should have wide casters. A protective mat should be used under all office chairs.
- Never use tape or other adhesive backed products on the surface.
- Just like natural bamboo, cork or wood floors your concrete floor can patina (discolor) with extended exposure to sunlight.